

ZT20J / ZT26J

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Highlights

- Premium work performance
- Zoomlion AWM Remote Monitoring and Rental Management System
- Smart telematic control interface with self-diagnostic capability

Features

Standard

- Horn
- All motion alarm
- Proportional control
- Self-closing entry gate
- Flashing amber beacon
- Auto-leveling system
- Emergency stop button
- Over tilt protection system
- Emergency descent system
- On-board diagnostic system
- Oscillating axle
- 4.3' LED display
- Load sensing system
- Swing-out engine tray
- Secondary Guarding System

Accessories & Options

- Platform work light
- AC power to platform
- Air line to platform
- Engine heater
- Low-temperature hydraulic oil
- Synthetic biodegradable hydraulic oil
- Non-marking tire





ZT20J / ZT26J

TELESCOPIC BOOM LIFTS

Comply with CE/ANSI/GB Standard

Technical data

Model	ZT20J	ZT26J
Size		
Work Height	22.75 m	28.2 m
Platform Height	20.75 m	26.2 m
Horizontal Outreach	16.8 m	22.71 m
A- Stowed Length	10.36 m	12.5 m
B- Stowed Width	2.49 m	2.49 m
C- Stowed Height	2.78 m	2.8 m
D- Platform Length	2.44 m	2.44 m
E- Platform Width	0.91 m	0.91 m
F- Wheelbase	2.52 m	3.05 m
Tread	2.13 m	2.11 m
G- Ground Clearance	0.42 m	0.4 m
Performance		
Platform capacity (Unrestricted / Restricted)	300kg / 454kg	300kg / 454kg
Drive Speed (Working)	6 km/h	5.5 km/h
Gradeability	45% (24°)	45% (24°)
Turning Radius (Inside)	2.4 m	3.66 m
Turning Radius (Outside)	5.4 m	6.86 m
Turret Swing	360° continuous	360° continuous
Platform Rotation	±90°	±90°
Tail Swing	1.45 m	1.6 m
Jib (Range of Articulation)	135° (-65° ~75°)	135° (-65° ~75°)
Max. Working Slope	3°	3°
Max. Wind Speed	12.5 m/s	12 m/s
Power		
Engine	Deutz D447 L4 / Perkins 404D-22T	Deutz TD.9 L4 / Cummins QSF2.8
Fuel Tank Capacity	130 l	150 l
Control Voltage	12V DC	12V DC
Hydraulic System Capacity	150 l	150 l
Drive Mode	4WD	4WD
Steering Mode	Front-wheel	Front-wheel
Tire		
Type	355/55D-625 Foam-filled tires	15-625 Foam Filled Tires
Weight		
Gross	12200 kg	18900 kg

